


Better BT-5890 Thermal Printer Specification:

 <p>Printing</p>	Print method	Direct thermal line
	Print width	58mm
	Dot density	384dot/line
	Print speed	90mm/s
	Interface	USB
	Paper diameter	65mm
	Line space	3.75mm(can be adjustive)
	Character Size	ANK Font Font A: 12×24dots Font B: 9×17dots Simplified/Traditional Chinese Character: 24×24dots
<p>Barcode</p>	Code page	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/ Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/ PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Barcode mode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128
	Fonts	GB2312
<p>Buffer</p>	Data	4K bytes
	NV Flash	60K bytes
<p>Power</p>	Cashdrawer out	DC 12V/1A
	Power supply	AC 110V/220V, 50 ~ 60Hz, DC 8.5V/3A
<p>Physical properties</p>	Weight	0.74kg
	Dimension	185×110×95mm
<p>Environment</p>	Work environment	Temperature:0 ~ 45℃, Humidity:10 ~ 80%
	Storage environment	Temperature:-10 ~ 60℃ , Humidity:10 ~ 90%